





QJMOTOR

TECHNICAL SPECIFICATION

Engine Type V-twin, 4-stroke, 8 Valves, DOHC

Bore x Stroke (mm) 58 x 47.2

Compression Ratio 10.3:1
Displacement (cc) 249

Cooling System Liquid-cooled

Ignition TLI

Maximum Power 27.5Hp at 9,000rpm

Maximum Torque 23.0Nm at 7,000rpm

Clutch Type Wet Multiplate with ASC

Fuel System Electronic Fuel Injection

Starter Electric

Transmission Chain, 6-speed

Front Suspension Upside Down Telescopic Forks

Rear Suspension Dual Shock

Front Brake Single Disc 280mm, ABS

Rear Brake Single Disc 240mm, ABS

Front Tyre 120/80-16

Rear Tyre 150/80-15

Overall Length (mm) 2,110

Overall Width (mm) 850

Overall Height (mm) 1,100

Seat Height (mm) 700

Wheelbase (mm) 1,400

Ground Clearance (mm) 160

Weight (kg) 163

Fuel Capacity (L') 13.5

Battery 12V8Ah

DIGITAL SPEEDOMETER

Easy to read at the first glance

FULL LED HEADLIGHTS

For brighter and clearer view

UPSIDE DOWN TELESCOPIC FRONT FORKS

Offer a more rigid set-up overall

FRONT DISC BRAKE + ABS

Single Disc 280mm with

Anti-lock Braking System (ABS)

ENGINE V-TWIN - 249cc, DOHC

Can produce maximum power 27.5Hp at 9,000rpm and maximum torque 23.0Nm at 7,000rpm

REAR SUSPENSION

Dual sock absorber that make the ride less bouncy

FUEL TANK 13.5-LITER

Give you more kilometre than you need

ERGONOMIC RIDING POSITION

Comfortable riding and steering for a longer travel distance

LED TAIL LIGHTS

Make you visible to other road users

REAR DISC BRAKE + ABS

Single Disc 240mm with Anti-lock Braking System (ABS)

COLOUR OPTIONS



MATTE BLACK

MATTE GREEN

Distributed by



MFORCE BIKE HOLDINGS SDN. BHD.(751410-H)

1485, Jalan Seruling, Kawasan Perindustrian Valdor, 14200 Sungai Jawi, Pulau Pinang, Malaysia. Tel: 604-545 2222 | Fax: 604-545 2288 | Email: help@mforce.my

